12 V

NOMAD POWER 400

Ref. 025882



The NOMAD POWER 400 is a lithium-based power pack that combines 3 functions:

- Booster for 12 V vehicles (motorbike, quad, car, SUV).
- Autonomous power supply for all kinds of electrical appliances.
- Emergency lamp.

LITHIUM BATTERY BOOSTER

Its **lithium** battery (*LiCoO2*) gives it an exceptional power-to-size ratio (starting current: 500 A).

It starts vehicles equipped with a discharged 12 V battery (*liquid, gel, AGM, Start&Stop*) in a few seconds (do not start Lithium LiFePO₄ batteries with this booster, battery voltages not compatible).



SAFETY START

The **smart jump lead** protects both the battery and the vehicle's electronics:

- Anti-spark technology,
- Short circuit protection,
- Reverse polarity protection,
- Protection against excessive starting currents,
- Protection against booster temperature increases.

MOBILE ENERGY SOURCE

Its storage capacity (3 Ah) gives it sufficient autonomy to meet the daily needs of staying connected (telephone, tablet, computer).

Equipped with:

- **2 USB ports :** 5 V / 9 V / 12 V 2 A / 5 V 2 A for recharging smartphone, tablet, GPS, etc.
- **1 output port 15 V 5 A** ideal for powering a 12 V electrical appliance (*cool box, fan, etc.*)

HIGH BRIGHTNESS ASSIST LAMP

Auxiliary light (1 led) with 3 lighting modes: normal, strobe, SOS.

LCD DISPLAY

The NOMAD POWER 400 is equipped with an LCD display that gives information on:

- the % of charge of the internal battery.
- the different input and output ports used.

A SMART PRODUCT

Lightweight (498 g) **and compact,** it will ideally find its place in a vehicle's glove box/tray as well as in a suitcase.



Colour LCD display



Supplied with case + accessories





Smart jump lead

Multiconnectors USB cable



Cigarette lighter adapter + charging cable

STARTING						EQUIPMENT						INPUT / OUTPUT				POWER BANK	LED	LED DIMENSIONS	
Lith		um	I		SMART CABLE	ı B	_	CABLES *			@	⊖→ OUTPUT			A n —	-\\-		<u> </u>	
Capacity per cell		Full charge	Start	Cranking CC	Peak Battery	ÜŢ			USB-C	MICRO USB Type B	Lightning	INPUT	***	12 V	15 V		- '^-	m	kg
	3 Ah 45 Wh	5 h	500 A	1000 A	1200 A	1	_	1	✓	1	1	5V-2A	5V-2A 2 — — — — 5/9/12V-2A	_	5 A	1	3 modes : Light SOS SPOT	17.5 x 8.4 x 3.1	0.498