

5,500 Lbs max /  
2.5T max



Powered exclusively by compressed air, the ERGO LIFT 1000 ROLL can lift and manoeuvre vehicles of up to 5,500 lb (2.5T) . With 4 support arms that swivel and lock automatically, it can be adapted to suit all chassis types. Ergonomically designed, it has a lifting height of around 1 m, so you can work upright around the vehicle to avoid fatigue.

- Super-compact: 4" (10 cm) in minimum position on the ground.
- Conforms to standard EN 1493 (load reversibility).
- Extremely useful in workshops with limited space.
- Mobile, can be manoeuvred easily with 4 wheels.




Work from a standing position to help prevent musculoskeletal injuries (MSDs).

Sturdy, highly stable, warp-resistant scissor construction.




Handle to position the support arms with an automatic locking system (with or without load).

Supplied with 8 rubber pads



4 large attachable wheels can be used to transform the lift into a mobile carriage, enabling the vehicle to be manoeuvred easily around the workshop.

Maintenance-free, detachable hydropneumatic pump.




All axles are fitted with bronze bushes with a self-lubricating coating, which require no maintenance.










Adjustable sliding skid on the support arms to leave the underbody accessible.

Hydraulic safety system with automatic scissor lock in the event of hose rupture.



## Optional accessories



 max	 minimum	 maximum	 3,307 lbs. 1,500 kg	 5,512 lbs. 2,500 kg	 max.		IP	 lbs. / kg	 89" / 226 cm 9.4" / 24 cm 45" / 115 cm product delivered on pallet
5,500 lbs. 2.5 T	4" / 10 cm	37" / 95 cm	45 sec.	60 sec.	116 PSI 8 bar	102" / 260 cm	IP54	880 396	950 lbs. (lift only)