

GYSMI 200P

- Welding unit with inverter technology piloted by microprocessor.
- The arc dynamic of the product is unique and revolutionary on the market.
- Can be used with all types of electrodes: rutile, basic, stainless steel, cast iron in direct current.
- Very handy, thanks to its small weight (5 kg) and its highly reduced volume.

• MMA

- ✓ Immediate start thanks to its very high no-load voltage
- ✓ Constant welding power
- ✓ Very smooth melting due to the direct current.
- ✓ No sensitive to supply current fluctuations or to the arc length.
- ✓ Very good penetration and perfect arc stability.

• ASSETS

- ✓ **ARC FORCE** : punctual increase of current in difficult welding situation.
- ✓ **HOT START** : increased power at start
- ✓ **ANTI STICKING** : anti sticking process.



LCD TECHNO 9-13 TRUE COLOR

 **High quality LCD:** UV/IR DIN 15 protection
Field of vision : 92 x 42 mm

 **Total weight:** 440 g

 **Power supply:** Solar

Filter:

- Initial shade : 4
- Welding shade: 9/13
- Arcing reaction time ≤ 0.3 ms
- Ideal for MMA/MIG-MAG : from 5 to 400 A
- Ideal for TIG : from 5 to 300 A



Ref. 031579

Delivered in bundle with:

- Earth cable (1,6 m / $\varnothing 16$ mm²)
- Electrode holder (2 m / $\varnothing 16$ mm²)
- LCD TECHNO 9/13 helmet TRUE COLOR



Ref. 030794

Delivered in suitcase with:

- Earth cable (1,6 m / $\varnothing 16$ mm²)
- Electrode holder (2 m / $\varnothing 16$ mm²)

50/60hz	-AM-	I ₂								EN60974-1 (40°C)		U ₀		
			$\varnothing 1.6$	$\varnothing 2$	$\varnothing 2.5$	$\varnothing 3.2$	$\varnothing 4$	$\varnothing 5$	I _A (60%)	X% (I ₂ max)	cm/kg			
230V 1~	32A	10-200A	62	50	47	45	30	21	110A	14%	72V	14x18x27 5	7 kW 10 kVA	