

The air-cooled MIG/MAG welding torches meet the needs of welders for a wide range of welding tasks. The GRIP handle's anti-slip coating and new ball joint provide you with exceptional working comfort.

DESCRIPTION



Torch designed for suction and evacuation of fumes at the source on the basis of standard MIG/MAG torches. Combined with a BINZEL filter vacuum cleaner or connected to a central vacuum system, the suction torch protects the welder's immediate environment.

FEATURES

- **Max current (Imax):** 230 A: CO₂ & 200A : Ar/CO₂
In pulsed mode, the capacity is reduced by 35%
- **Duty cycle:** 230 A @ 60 %
- **Recommended wire diameter:** 0.8 to 1.2 mm
- **Length:** 3 m



CONSUMABLES

Torch



Contact tube supports & diffusers



042995




042919

Contact tubes



Ø 0.6	041905
Ø 0.8	041950 ●
Ø 1.0	041967
Ø 1.2	041974

Nozzles



aspiration

Ø 15 040571

+



welding

Ø 15 041882

Sheath

	Ø 0.6/0.8		Ø 1.0 & 1.2		Ø 1.2 & 1.6	
	3 m	4 m	3 m	4 m	3 m	4 m
Steel	041592 ●	041837	041608	041844	418417	418424
Teflon	041578	044050	041585	044067	-	044074
Carbon	-	039834	-	039827	-	039810

Consumables box option:

Ref. 041233

	x5
	x3
	x5 (M6-Ø 0.6)
	x5 (M6-Ø 0.8)
	x5 (Alu-M6-Ø 1.0)
	x3



- Originele apparatuur