

MIG/MAG welding torches in air-cooled version are the perfect answer to the needs of welders for the execution of the most diverse jobs. The non-slip coating and the new ball joint of the GRIP handle provide you an exceptional working comfort.

DESCRIPTION



Torch designed for suction and fume extraction at the gas source on the principle of the standard MIG/MAG torches. Combined with a BINZEL filter vacuum cleaner or connected to a central vacuum system, the suction torch protects the welder's immediate environment.

FEATURES

- **Max current (I_{max})** : 300 A : CO₂ and 270 A : Ar/CO₂
In pulsed mode, these capacities are reduced by 35%
- **Duty cycle**: 300 A @ 60 %
- **Recommended wire diameters**: 0,8 to 1,2 mm
- **Length**: 4 m



CONSUMABLES

Torch



Tip support & diffusers Torch



STEEL/ALU
043008



STEEL/ALU
042926

Contact tubes



	STEEL	ALU
Ø 0.8	041790	-
Ø 1.0	419803	419766
Ø 1.2	419810	419773
Ø 1.4	419827	
Ø 1.6	419834	

Nozzles



Suction

Ø 16 | 040588

+



welding

Ø 16 | 041783

Liners

	Ø 0.6/0.8		Ø 1.0 & 1.2		Ø 1.2 & 1.6	
	3 m	4 m	3 m	4 m	3 m	4 m
Steel	041592	041837	041608	041844	418417	418424
Teflon	041578	044050	041585	044067	-	044074
Carbon	-	039834	●	039827	-	039810

Consumables box option:

Ref. 041417

	x2
	x3
	x5 (M8-Ø 1.0)
	x5 (M8-Ø 1.2)
	x5 (Alu-M8-Ø 1.0)
	x5 (Alu-M8-Ø 1.2)
	x3

