

The liquid-cooled MIG/MAG welding torches meet the needs of welders for a wide range of welding tasks. The GRIP handle's anti-slip coating and new ball joint provide you with exceptional working comfort.

DESCRIPTION

Extremely resistant torch.
Torch for use in heavy boilermaking and structural steel work.
Ergonomic handle with «GRIP» coating ensures a secure grip even in difficult positions.

FEATURES

- **Max current (Imax):** 500 A: CO2 and 450 A: Ar/CO2
In pulsed mode, these capacities are reduced by 35%.
- **Duty cycle:** 450 A @ 100 %.
- **Recommended wire diameters:** 1.0 to 2.4 mm
- **Lengths:** 3 m, 4 m & 5 m



CONSUMABLES

Torch



Contact tube supports & diffusers

STEEL	ALU	STEEL	ALU
042940		043022	

Contact tubes

	STEEL	ALU
Ø 0.8	041790	-
Ø 1.0	419803	419766
Ø 1.2	419810 ● ●	419773 ● ●
Ø 1.4	419827	-
Ø 1.6	419834	041080
Ø 2.4	040533	-

Nozzles

	STEEL	ALU
Ø 16	042315	

Sheath

	Ø 0.6/0.8			Ø 1.0 & 1.2				Ø 1.2 & 1.6			Ø 1.6 & 2.4	
	3 m	4 m	5 m	3 m	4 m	5 m	8 m	3 m	4 m	5 m	4 m	5 m
Steel	-	041837	-	041608	041844 ●	062276 ●	-	418417	418424	062283	040526	062290
Teflon	041578	044050	-	041585	044067	-	038677	-	044074	-	-	-
Carbon	-	039834	062306	●	039827 ●	062313	-	-	039810	-	-	-

- Original steel equipment 4 m
- Original aluminium equipment 3 m
- Original steel equipment 5 m
- Original aluminium equipment 4 m