

Lightweight and easy to use, these torches offer great manoeuvrability for smooth welding. The molded handle provides optimal grip to achieve the perfect weld. Thanks to its small size, the SR 9 torch is particularly recommended for precision work on thin workpieces.

FEATURES

BASIC SR 9

Cooling: Air
Capacity:

- direct current (DC): 110 A
- in alternating current (AC): 95 A

Duty cycle: 60%.

Tungsten electrode: Ø 0.5 - 1.6 mm



GRIP SR 9

Cooling: Air
Capacity:

- direct current (DC): 110 A
- in alternating current (AC): 80 A

Duty cycle: 35%.

Tungsten electrode: Ø 0.5 - 1.6 mm



CONFIGURATIONS

	Connector		L	DB	
			—	GRIP	
			I (m)	Ref	
Ø 10/25	DIN		4m	044432	—
			8m	044333	—
			4m	—	—
Ø 35/50	AMPHENOL		8m	044326	046016
				039421	

L Trigger

DB Double button

Included

All the necessary consumables for your TIG SR9 torch in one box:



- 2 nozzles (N4 and N6)
- 1 collar support Ø1.6
- 1 vice pliers Ø1.6
- 2 caps (1 short + 1 long)
- 1 tungsten electrode WR2 AC/DC Ø1.6

• Also available for sale without the torch (ref. 044654)

CONSUMABLES

	Nozzle	Collar support	Standard insulating ring	Collet	head cover
STANDARD ASSEMBLY					
	N 4 - Ø 6.5 (x3) 044876	Ø 1.6 (x3) 044838	(x1) 044890	Ø 1.6 (x3) 044852	Courte (x1) 044814
	N 5 - Ø 8.0 (x3) 038356	Ø 2.0 (x3) 045149		Ø 2.0 (x3) 045132	Longue (x1) 044821
	N 6 - Ø 9.5 (x3) 044883	Ø 2.4 (x3) 044845		Ø 2.4 (x3) 044869	
	N 7 - Ø 11 (x3) 038363	Ø 3.2 (x3) 045248		Ø 3.2 (x3) 045255	
	N 8 - Ø 12.5 (x3) 045170				
N 10 - Ø 16 (x3) 038370					
PRO MOUNTING					
	N 4 - Ø 6.5 (x3) 044920	Ø 1.6 (x2) 044906	(x1) 044890	Ø 1.6 (x3) 044852	Courte (x1) 044814
	N 6 - Ø 9.5 (x3) 044937	Ø 2.0 (x2) 045156		Ø 2.0 (x3) 045132	Longue (x1) 044821
	N 7 - Ø 11 (x3) 045262	Ø 2.4 (x2) 044913		Ø 2.4 (x3) 044869	
		Ø 3.2 (x2) 045279		Ø 3.2 (x3) 045255	

RECOMMENDATIONS

	TIG 160 DC	TIG 168 DC	TIG 200 DC FV	TIG 220 DC FV	TIG 300 DC	TIG 207 AC/DC FV	TIG 208 AC/DC	TIG 220 AC/DC	TIG 250 AC/DC
SR9 connection 10/25 + DIN	✓	—	—	—	—	—	—	—	—
SR9 connection 35/50 + DIN	—	✓	—	—	—	—	—	—	—
SR9 connection 35/50 + AMPHENOL				compatible				compatible	