

Lightweight and easy to use, these torches offer ideal manoeuvrability for smooth welding. The Ergonomic handle design provides optimal grip to achieve the perfect weld. The SR 26 torch is the most powerful in the air-cooled range.

## FEATURES

### SR 26 BASIC

**Cooling:** Air  
**Capacity:**

- in direct current (DC): 240 A
- in alternating current (AC): 200 A

**Duty cycle:** 60% Duty cycle

**Tungsten electrode:** Ø 0.5 - 4.0 mm



### SR 26 GRIP

**Cooling:** Air  
**Capacity:**

- in direct current (DC): 180 A
- in alternating current (AC): 130 A


**Duty cycle:** 35% Duty cycle

**Tungsten electrode:** Ø 0.5 - 4.0 mm



## CONFIGURATIONS

Connector	L	DB	P	l (m)	Ref		
					GRIP	GRIP	GRIP
Ø 35/50 DIN	4m	044463	046054	046115			
					8m	044371	046078
Ø 35/50 AMPHENOL	4m	038271					
		8m	046184	046177	047877		



## INCLUDED

All the essential consumables for your TIG AC/DC SR26 torch in a box:

- 2 Gas nozzles (N5 and N7)
- 2 collets body (Ø1.6 + Ø2/2.4)
- 2 collet (Ø1.6 + Ø2.4)
- 2 caps (1 short + 1 long)
- 2 tungsten electrodes WR2 AC/DC (Ø1.6 + Ø2.4)

• Also available for sale without the torch (ref. 044678)

## CONSUMABLES


STANDARD ASSEMBLY

Nozzle



N 4 - Ø 6.5	(x3)	038394
N 5 - Ø 8.0	(x3)	045026
N 6 - Ø 9.5	(x3)	038400
N 7 - Ø 11	(x3)	045033
N 8 - Ø 12.5	(x3)	045286
N 10 - Ø 16	(x3)	045293
N 12 - Ø 19	(x3)	045309

Collet body



Ø 1.6	(x3)	044968
Ø 2.0/2.4	(x3)	044975
Ø 3.2	(x3)	045118
Ø 4	(x3)	047648

Standard insulating ring



(x1)	045040
------	--------

Collet



Ø 1.6	(x3)	044982
Ø 2.0	(x3)	044999
Ø 2.4	(x3)	045019
Ø 3.2	(x3)	045125
Ø 4	(x3)	047655

Head cover



Courte	(x1)	044944
Longue	(x1)	044951


PRO MOUNTING

Diffuser nozzle



N5 - Ø 8.0	(x3)	045071
N7 - Ø 11	(x3)	045088

Support for diffuser collar



Ø 1.6	(x2)	045057
Ø 2.0/2.4	(x2)	045064

Insulating ring diffuser




(x1)	045095
------	--------

Standard insulating ring



(x1)	045040
------	--------

Collet



Ø 1.6	(x3)	044982
Ø 2.0	(x3)	044999
Ø 2.4	(x3)	045019
Ø 3.2	(x3)	045125
Ø 4	(x3)	047655

Head cover



Short	(x1)	044944
Long	(x1)	044951

## RECOMMENDATIONS

SR26	TIG 160 DC	PROTIG 161	PROTIG 200	PROTIG 201	TIG 220	TIG 300	TITAN		PROTIG 201 AC/DC	TIG 220 AC/DC	TIG 250 AC/DC	TITANIUM		EXATIG
							320	400				320	400	
35/50 + DIN														
35/50 + AMPHENOL		✓	✓	✓	✓	✓	✓		✓	✓		✓		✓
EURO	Recommended for MIG/MAG generators with TIG function													