

Lightweight and easy to use, these torches offer great manoeuvrability for smooth welding. The molded handle with GRIP provides optimal grip to achieve the perfect weld. In combination with a TIG machine and cooling unit, the SR 20 torch is designed for production welding.

FEATURES


BASIC SR 20

Cooling: Liquid
Capacity:

- direct current (DC): 220 A
- in alternating current (AC): 200 A

Duty cycle: 100 %

Tungsten electrode: Ø 0.5 - 3.2 mm



GRIP SR 20

Cooling: Liquid
Capacity:

- direct current (DC): 220 A
- in alternating current (AC): 150 A

Duty cycle: 100 %

Tungsten electrode: Ø 0.5 - 3.2 mm



CONFIGURATIONS

Connector		L	DB	P	
		GRIP	GRIP		
Ø 35 / 50	DIN	4m	046061	—	
		8m	044357	046023	046139
Ø 35 / 50	AMPHENOL	4m	—	038202	—
		8m	046153	046146	047860



L Trigger



P Double button and Potentiometer



DB Double Button

INCLUDES

All the necessary consumables for your TIG AC/DC SR20 torch in one box:

- 2 nozzles (N4 and N6)
- 2 collar supports (Ø1.6 + Ø2.4)
- 2 vice pliers (Ø1.6 + Ø2.4)
- 2 caps (1 short + 1 long)
- 2 tungsten electrodes WR2 AC/DC (Ø1.6 + Ø2.4)

• Also available for sale without the torch (ref. 044685)

CONSUMABLES

STANDARD ASSEMBLY	Nozzle	Collar support	Standard insulating ring	Collet	head cover																																																	
	<table border="1"> <tr><td>N 4 - Ø 6.5</td><td>(x3)</td><td>044876</td></tr> <tr><td>N 5 - Ø 8.0</td><td>(x3)</td><td>038356</td></tr> <tr><td>N 6 - Ø 9.5</td><td>(x3)</td><td>044883</td></tr> <tr><td>N 7 - Ø 11</td><td>(x3)</td><td>038363</td></tr> <tr><td>N 8 - Ø 12.5</td><td>(x3)</td><td>045170</td></tr> <tr><td>N 10 - Ø 16</td><td>(x3)</td><td>038370</td></tr> </table>	N 4 - Ø 6.5	(x3)	044876	N 5 - Ø 8.0	(x3)	038356	N 6 - Ø 9.5	(x3)	044883	N 7 - Ø 11	(x3)	038363	N 8 - Ø 12.5	(x3)	045170	N 10 - Ø 16	(x3)	038370	<table border="1"> <tr><td>Ø 1.6</td><td>(x3)</td><td>044838</td></tr> <tr><td>Ø 2.0</td><td>(x3)</td><td>045149</td></tr> <tr><td>Ø 2.4</td><td>(x3)</td><td>044845</td></tr> <tr><td>Ø 3.2</td><td>(x3)</td><td>045248</td></tr> </table>	Ø 1.6	(x3)	044838	Ø 2.0	(x3)	045149	Ø 2.4	(x3)	044845	Ø 3.2	(x3)	045248	<table border="1"> <tr><td>(x1)</td><td>044890</td></tr> </table>	(x1)	044890	<table border="1"> <tr><td>Ø 1.6</td><td>(x3)</td><td>044852</td></tr> <tr><td>Ø 2.0</td><td>(x3)</td><td>045132</td></tr> <tr><td>Ø 2.4</td><td>(x3)</td><td>044869</td></tr> <tr><td>Ø 3.2</td><td>(x3)</td><td>045255</td></tr> </table>	Ø 1.6	(x3)	044852	Ø 2.0	(x3)	045132	Ø 2.4	(x3)	044869	Ø 3.2	(x3)	045255	<table border="1"> <tr><td>Courte</td><td>(x1)</td><td>044814</td></tr> <tr><td>Longue</td><td>(x1)</td><td>044821</td></tr> </table>	Courte	(x1)	044814	Longue	(x1)
N 4 - Ø 6.5	(x3)	044876																																																				
N 5 - Ø 8.0	(x3)	038356																																																				
N 6 - Ø 9.5	(x3)	044883																																																				
N 7 - Ø 11	(x3)	038363																																																				
N 8 - Ø 12.5	(x3)	045170																																																				
N 10 - Ø 16	(x3)	038370																																																				
Ø 1.6	(x3)	044838																																																				
Ø 2.0	(x3)	045149																																																				
Ø 2.4	(x3)	044845																																																				
Ø 3.2	(x3)	045248																																																				
(x1)	044890																																																					
Ø 1.6	(x3)	044852																																																				
Ø 2.0	(x3)	045132																																																				
Ø 2.4	(x3)	044869																																																				
Ø 3.2	(x3)	045255																																																				
Courte	(x1)	044814																																																				
Longue	(x1)	044821																																																				

PRO MOUNTING	Diffuser nozzle	Support for diffuser collar	Standard insulating ring	Collet	head cover																																								
	<table border="1"> <tr><td>N 4 - Ø 6.5</td><td>(x3)</td><td>044920</td></tr> <tr><td>N 6 - Ø 9.5</td><td>(x3)</td><td>044937</td></tr> <tr><td>N 7 - Ø 11</td><td>(x3)</td><td>045262</td></tr> </table>	N 4 - Ø 6.5	(x3)	044920	N 6 - Ø 9.5	(x3)	044937	N 7 - Ø 11	(x3)	045262	<table border="1"> <tr><td>Ø 1.6</td><td>(x2)</td><td>044906</td></tr> <tr><td>Ø 2.0</td><td>(x2)</td><td>045156</td></tr> <tr><td>Ø 2.4</td><td>(x2)</td><td>044913</td></tr> <tr><td>Ø 3.2</td><td>(x2)</td><td>045279</td></tr> </table>	Ø 1.6	(x2)	044906	Ø 2.0	(x2)	045156	Ø 2.4	(x2)	044913	Ø 3.2	(x2)	045279	<table border="1"> <tr><td>(x1)</td><td>044890</td></tr> </table>	(x1)	044890	<table border="1"> <tr><td>Ø 1.6</td><td>(x3)</td><td>044852</td></tr> <tr><td>Ø 2.0</td><td>(x3)</td><td>045132</td></tr> <tr><td>Ø 2.4</td><td>(x3)</td><td>044869</td></tr> <tr><td>Ø 3.2</td><td>(x3)</td><td>045255</td></tr> </table>	Ø 1.6	(x3)	044852	Ø 2.0	(x3)	045132	Ø 2.4	(x3)	044869	Ø 3.2	(x3)	045255	<table border="1"> <tr><td>Courte</td><td>(x1)</td><td>044814</td></tr> <tr><td>Longue</td><td>(x1)</td><td>044821</td></tr> </table>	Courte	(x1)	044814	Longue	(x1)
N 4 - Ø 6.5	(x3)	044920																																											
N 6 - Ø 9.5	(x3)	044937																																											
N 7 - Ø 11	(x3)	045262																																											
Ø 1.6	(x2)	044906																																											
Ø 2.0	(x2)	045156																																											
Ø 2.4	(x2)	044913																																											
Ø 3.2	(x2)	045279																																											
(x1)	044890																																												
Ø 1.6	(x3)	044852																																											
Ø 2.0	(x3)	045132																																											
Ø 2.4	(x3)	044869																																											
Ø 3.2	(x3)	045255																																											
Courte	(x1)	044814																																											
Longue	(x1)	044821																																											

RECOMMENDATIONS

	TIG 160 DC	TIG 168 DC	TIG 200 DC FV	TIG 220 DC FV	TIG 300 DC	TIG 207 AC/DC FV	TIG 208 AC/DC	TIG 220 AC/DC	TIG 250 AC/DC
SR20 connection 35/50 + DIN	—	—	—	—	—	✓	✓	—	—
SR20 connection 35/50 + AMPHENOL	—	—	—	✓	✓	—	—	✓	✓