

The liquid-cooled MIG/MAG welding torches meet the needs of welders for a wide range of welding tasks. The GRIP handle's anti-slip coating and new ball joint provide you with exceptional working comfort.

## DESCRIPTION

Extremely resistant torch.

Torch for use in heavy boilermaking and structural steel work.

Ergonomic handle with «GRIP» coating ensures a secure grip even in difficult positions.

## FEATURES

- **Max current (Imax):** 500 A: CO2 and 450 A: Ar/CO2  
*In pulsed mode, these capacities are reduced by 35%.*
- **Duty cycle:** 450 A @ 100 %.
- **Recommended wire diameters:** 1.0 to 2.4 mm
- **Lengths:** 3 m, 4 m & 5 m



## CONSUMABLES

### Torch



### Contact tube supports & diffusers



STEEL	ALU
042940	



STEEL	ALU
	043022

### Contact tubes



	STEEL	ALU
Ø 0.8	041790	-
Ø 1.0	419803	419766
Ø 1.2	419810 ● ●	419773 ● ●
Ø 1.4	419827	-
Ø 1.6	419834	041080
Ø 2.4	040533	-

### Nozzles



	STEEL	ALU
Ø 16	042315	

## Sheath

	Ø 0.6/0.8			Ø 1.0 & 1.2				Ø 1.2 & 1.6			Ø 1.6 & 2.4	
	3 m	4 m	5 m	3 m	4 m	5 m	8 m	3 m	4 m	5 m	4 m	5 m
Steel	-	041837	-	041608	041844 ●	062276 ●	-	418417	418424	062283	040526	062290
Teflon	041578	044050	-	041585	044067	-	038677	-	044074	-	-	-
Carbon	-	039834	062306	●	039827 ●	062313	-	-	039810	-	-	-

- Original steel equipment 4 m
- Original aluminium equipment 3 m

- Original steel equipment 5 m
- Original aluminium equipment 4 m