


The **GYSDUST EXTRACTOR** is a pneumatic dust-extraction unit for sanding-dust designed specifically for car-body repair. This brand-new suction system, developed by GYS' expert engineers, combines high suction performance with low air consumption. ATEX certified, this appliance is suitable for aluminium sanding-dust from car-body repairs.

MAIN ADVANTAGES

- **Efficient:** This powerful GYS suction system achieves high suction levels with low air consumption.
- **ATEX certified:**
 - suitable for explosive atmospheres
 - suitable for using abrasives on aluminium car bodies
- **Practical:** its two large \varnothing 150 mm wheels make it easy to move around the workshop.
- **Easy to use:** no maintenance required. No moving parts. No filter to clean.
- **Adjustable sanding pressure** and pressure gauge meaning this machine can be used with all types of commercial sander.



ACCESSORIES INCLUDED



1 earth clamp




1 dust bag
(PN. 058880 - 5 bags)



1 hose 3 m
| \varnothing 29 mm



ATEX kategori
Gruppe II - Kategori 3



OPTIONAL SANDER



**Pneumatic orbital sander
with \varnothing 150 mm buffing pad
MIRKA PRO S 650HP
PN. 071346**

FEATURES

Bag capacity	5 kg
Air flow	600 l/mn
Air consumption	340 l/mn
Suction power	1 150 mm H2O
Noise level	70 dB (A)
Hose dimensions	\varnothing 29 mm 3 m long