

The KRYPTON 231 DC FV is a professional 230A single-phase TIG power source with IP23S protection, designed to endure demanding operating conditions. Its advanced technology delivers a totally stable arc and superior weld quality, and its high duty cycle is ideal for industrial and robotic applications.

2 WELDING PROCESSES

- | | |
|--------|---|
| TIG DC | DC Standard: smooth current welding on most ferrous materials. |
| TIG DC | DC Pulse, up to 2 kHz: limits the temperature of the weld pool, reduces deformation and allows the assembly of thin sheet materials from 0.3 mm. |
| MMA | Standard MMA: coated, rutile, basic and cellulosic electrodes (up to Ø 5 mm). |
| MMA | MMA Pulse, up to 500 Hz: facilitates welding in a vertical upright direction (tubes/pipelines, etc.) |



Supplied without accessories

ENHANCED TIG SETTINGS

- **TIG duty cycle 100% at 200 A**
- **4 spot modes:**
 - Spot / Multi Spot : traditional spot welding before joining thin sheets.
 - Tack / Multi Tack : ultra-precise and oxidation-free tacking reducing the risk of deformation.
- **3 types of ignition:** Lift, HF and Touch.HF (timed high frequency ignition).
- **3 trigger management options:** 2T, 4T and 4T LOG
- **Pulse TIG waveform settings for arc control and penetration.**
- **E-Weld mode** ensures that the unit delivers the required welding power regardless of the position of the torch in relation to the workpiece (control of welding energy).

MAXIMUM CONNECTIVITY

- Accurately measuring power supply.
- Calibration mode for welding accessories (refines calculation of power usage).
- Ready for robotic integration via an optional kit (037960).
- Storage of up to 50 programs per process for recurring tasks.
- Compatible with slat, dual button, potentiometer and Up & Down torches.
- Full machine updates available via USB stick.
- Remote controls (foot switch or optional manual) connectable without the use of tools.
- Optional cooling unit (070820) with easy and tool-free installation.
- VRD can be activated to lower the no-load output voltage < 35 V.
- «FV» technology maintains a stable arc in case of mains voltage variations (85-265 V), power supplied via a generator, or when using very long power cables.



Dual display user interface with rotary knob and push button for fast adjustment of parameters

IDEAL ON SITE

- Suitable for extension cords up to 100m.
- Reinforced construction and anti-shock feet.
- IP23S rating
- Space-saving and easy to move on site.
- Protected against overvoltage up to 400 V (PROTEC 400).

ACCESSORIES (optional)

 TIG torch - 8 m SR26L SR26DB 046184 046177		 Cooling unit 1000 W 3 L - 14 kg KOOLWELD 1 070820		 Quick fixing kit 076006		 Trolley 10m ³ 076341		Analogue remote controls:  RC-HA1 - 8 m 045675		 RC-FA1 - 4 m 045682		Digital remote controls:  +  RC-HD2 062122		Kit NUM-1 063938	
--	--	--	--	---	--	---	--	---	--	---	--	---	--	---------------------	--

50/60 Hz	A	I ₂ TIG	I ₂ MMA	INTEGRATED TECHNOLOGY		TIG			MMA			U ₀	U _R	mm ²	cm	kg	IP	Protected & compatible power generator (+/-15%)	
				TIG DC PULSE	MMA PULSE	EN 60974-1 (40°C)			EN 60974-1 (40°C)										
110 V - 1~	32	3 → 140	5 → 120	0.1 → 2 kHz	0.4 → 500 Hz	IA (60%)	X% (I ₂ max)	100%	IA (60%)	X% (I ₂ max)	100%	V	V	35/50	49 x 26 x 40 cm	16.5	IP23S	2 m	12.5 kVA
230 V - 1~	16	3 → 230	5 → 230			120 A	40 %	100 A	85 A	23 %	70 A	69	31 (VRD)						